

Unicont PDF
Field mounting indicator. Loop powered.

MODEL	DESCRIPTION	PRICE
PDF-401	Field mounting indicator. Loop powered. Mount: Wall mount. Temperature: -25~60°C. Housing: Paint coated aluminium. Display: 6 digit LCD, engineering units and bar graph. Power: 2 wire, 4~20mA. Option, 4 wire, 4~20mA/HART. Protection: IP67.	\$885.00
PDF-401 Ex marking	Field mounting indicator. Ex version. Specifications as above. Ex 112GEExia11CT6 / Ex 11GEExd11BT6.	POA
PDF-501	Housing Option: reinforced plastic. Not available in Ex version.	\$830.00



LR-Display
Plug in Display. Loop powered.

MODEL	DESCRIPTION	PRICE
LR-Display	Plug in Display. Loop powered. Input: 4~20mA, 2 wire. Display: 4-digit: 7.6mm height. Housing: Plastic. Protection: IP65.	\$290.00



LR-Display shown with
 JUMO P30-504 Pressure
 Transmitter - see page 60.

LPI-LCD-5
Panel Mount Indicator. Loop powered.

www.intech.co.nz/lpi-lcd

MODEL	DESCRIPTION	PRICE
LPI-LCD-5	Panel mount. Loop powered. Input: 4~20mA, 2 wire. Display: 5-digit LCD of 12.5mm height. Volts Drop: 3.9V @ 20mA. Scaling: Programmable between -19999 to 30000. Max Resolution: 50,000 counts. Accuracy: +/-0.02% of reading plus 2 digits. Decimal Point: Programmable to six positions. Temperature: -10°C to +50°C. Protection: IP65. Housing: Plastic. 96 x 48mm.	\$348.00
Cover	Option: Splash proof lockable security cover: IP65	\$72.00



Unicont PKK
Multifunction limit switch.

MODEL	DESCRIPTION	PRICE
PKK-312	Loop current monitoring relay and digital isolator. Mount: DIN rail. Operating modes: (selectable) Limit switch, Differential switch, Window switch. Supply voltage: 230, 110, 24Vac. 24Vdc. Specify one when ordering. Input: 1~22mA & dry contact. Output: Relay, 8 amps, 250Vac. Transmitter Power Supply: 30v, I _{max} = 70mA.	\$275.00

