

Level instruments



Roto-Bin-Dicator®

MODEL	DESCRIPTION	PRICE
RXC-H	Roto-Bin-Dicator® Explosion Proof. Complete with type 1 or type 2 paddle. Dry bulk level control. Mounting plate: Wall mount. Pipe mount optional. Temperature: -10~70°C. Output relay: 10amp SPDT. Power supply: 230Vac. Protection: IP67. Rating: NEMA 7/9. Flexible neoprene shaft drive. Extended shaft fittings available. (LAR101080)	\$935.00
RB-H	Specifications as above but not explosion proof. Rating: NEMA 4X. (LAR101020)	\$830.00
R-24VDC	Option 24Vdc version of RB-H. <i>Add</i> (LAR101011)	\$200.00
RSSP2G	Roto-Bin-Dicator® Super-Safe-Plus. Complete with type 1 or type 2 paddle. Dry bulk level control. Specifications as above but with: Time relay. Fail safe selection for power. High and low level failure alarm outputs. Rating: NEMA 4X. (LAR100413)	\$1145.00
RB Parts		
H-371	Paddle type 1, 4 vane, 2"x 7", 304SS. (LAR110360)	\$65.00
H-370	Paddle type 2, 4 vane, 1.5"x 5", 304SS. (LAR110310)	\$62.00
H-372	Paddle type 3, 1 vane, 1"x 2.8", 304SS. (LAR110400)	\$68.00
H-36	Neoprene flexible shaft. (LAR110270)	\$65.00
A-H-9D-K-HD	Motor 220Vac Kit. (LAR110100)	\$230.00
A-H-9A-K-HD	Motor 110Vac Kit. (LAR110070)	\$225.00
	Other parts are available, please enquire.	

www.intech.co.nz/bindicator

Mini Roto-Bin-Dicator®



MODEL	DESCRIPTION	PRICE
MR-2-Y	Mini Roto-Bin-Dicator® <i>Level sensing of light granular solids in small bins and hoppers,</i> <i>i.e.: plastics, granular foods, sugar, cereals and seeds.</i> Designed to shut the motor off during the presence of materials. Adjustable sensitivity allowing the use in varying material density. LED indication is visible from 15m. Mounting: 3/4" NPT. Temperature: -40~93°C. Output relay: 10amp 250Vac. Power supply: 230Vac. Protection: IP67. Paddle: Nylon (polysulfone).	\$465.00
Parts		
LMR120003	Insertable paddle (banana shaped).	\$25.00
LMR120006	4 vane paddle.	\$20.00
LMR130006	Motor 240Vac.	\$125.00
LMR130005	Motor 120Vac.	\$125.00
	Other parts are available, please enquire.	

OTHER BINDICATOR PRODUCTS:

CAPACITIVE RF PROBES	CAPACITIVE RF PROBES	DIAPHRAGM SWITCHES	RADAR TRACKING
-Point level switching. -Self calibrating. -Standard and High temperature.	-Continuous level transmitters. -Standard and High temperature.	-Point level switching.	-Continuous level transmitters. -Standard and High temperature.

Sepra-lite series

Integral optic level switches

Mount:	1/2" NPT. IP66.	
Temperature:	-40~85°C.	
Output:	NPN open collector.	11~26Vdc. 100mA.
	Cable 5 metres.	
MODEL	DESCRIPTION	PRICE
GLL100501A	Brass body and Quartz window. Pressure: 600 PSI.	\$498.00
GLL100504A	PFA Teflon body and window. Pressure: 100 PSI.	\$568.00



- ◆ LED alarm indicator.
- ◆ Clean liquids.
- ◆ Corrosive liquids.
- ◆ High pressure.
- ◆ Oil levels.
- ◆ Adjustable sensitivity.
- ◆ Senses any transparent or translucent liquid.
- ◆ Output includes selectable wet or dry sinking.
- ◆ Self contained level switch with removable electronics.

Optic Level Switch

Two part optic level switches.

MODEL	DESCRIPTION	PRICE
Controllers.	High or low fail safe adjustment. LED alarm status. Sensitivity adjustment. Input: Optic probes. Output: 2 relays. 10amp SPDT. Time delay: Adjustable 1~60 seconds. Power supply: 240Vac. 50/60Hz.	
GLL101S2N	Optic Level Switch Controller. 1 channel.	\$545.00
GLL102S2N	Optic Level Switch and Pump Controller. 2 channels.	\$665.00
Probes.	Mount: 1/2" NPT. Pressure: 100 PSI. Temperature: -29~94°C. Output: Connect to controller.	
GLL110010	PFA Teflon Optic Probe. For any corrosive or high purity liquid. Made from non-stick teflon to prevent coating.	\$650.00
GLL110000	Polysulfone Optic Probe. For most oil, water and mildly corrosive applications.	\$520.00
GLL110118	Polysulfone Optic Sanitary Probe. Mount: 1/2" Tri-clover. Food and pharmaceutical industries.	\$970.00

