

RPM/Rate meters, Totalisers, Power Meters

RPM/Rate/Hz meter



Programmable digital RPM/Rate/Hz meter.

Digits: 4 digit LED.
 Power supply: 110/220Vac.
 Sensor power: 12Vdc, 60mA.
 Prescaler: 000.001 ~ 999.999.
 Range: 4.0 ~ 3000.
 Input: Solid state, 3k3 Hz max..

MODEL	SIZE	PRICE
R1-4DO	96 x 48	\$213.00

Totaliser



Digital totaliser.

Digits: 8 digit LCD.
 Power supply: Battery - 3 year life.
 Mode: Up count.
 Input: **-MC** Contact, 10 Hz max.
 -MA 80~250Vac, 10 Hz max.
 -MD 6~30Vdc, 10 Hz max.
 Reset: External.
 For front panel reset, add.....\$6.00

MODEL	SIZE	PRICE
LC8-	31 x 56	\$55.00

Hours run



Digital hours run meter.

Digits: 8 digit LCD.
 Power supply: Battery - 3 year life.
 Range: 9999 hours 59 min.
 Input: **-MC** Contact on/off.
 -MA 80~250Vac.
 -MD 6~30Vdc.
 Reset: External.
 For front panel reset, add.....\$6.00

MODEL	SIZE	PRICE
LT8-	31 x 56	\$55.00

Current Meter



AC Amps Digital Indicator.

Display: 4 digit, 15mm high.
 Programmable.
 Power supply: 110~230Vac.
 Input: 0~5 Amps.

MODEL	SIZE	PRICE
PM491 AAC	96 x 48	\$138.00

Volt Meter



AC Volts Digital Indicator.

Display: 4 digit, 15mm high.
 0~500Vac
 Power supply: 110~230Vac.
 Input: 0~500Vac.

MODEL	SIZE	PRICE
PM491 VAC	96 x 48	\$138.00

Proximity sensors

MODEL	DESCRIPTION	PRICE
	Inductive proximity sensor with LED indicator. Power supply: 12~24Vdc. 10mA. Temperature: -20~70°C.	
PL-X1204N	Range: 4 mm. Dimension: 60 x Ø12mm. Output: NPN 100mA.	\$45.00
PL-X1204P	Output: PNP 100mA.	\$45.00
PL-X5P	Range: 5 mm. Dimension: 60 x Ø18mm. Output: PNP 100mA.	\$58.00
PR-10P	Range: 10 mm. Dimension: 90 x Ø30mm. Output: PNP 100mA.	\$85.00





MODEL	DESCRIPTION	PRICE
	Inductive proximity sensor with LED indicator. Power supply: 12~24Vdc. 10mA. Temperature: -20~70°C.	
PL-4P	Range: 4 mm. Dimension: 18 x 18 x L35mm. Output: PNP 100mA.	\$25.00
PL-H5P	Range: 5 mm. Dimension: 18 x 18 x L38mm. Output: PNP 100mA.	\$28.00
PL-10P	Range: 10 mm. Dimension: 30 x 30 x L53mm. Output: PNP 100mA.	\$50.00



MODEL	DESCRIPTION	PRICE
	Photo diffusion reflective sensor with LED indicator. Power supply: 12~24Vdc. 30mA. Temperature: -20~70°C.	
RS5 10P	Range: 100 mm. Dimension: 80 x Ø18mm. Output: PNP 100mA.	\$95.00
RS-V30PN	Range: 300 mm. Dimension: 80 x Ø18mm. Output: PNP 100mA.	\$95.00



MODEL	DESCRIPTION	PRICE
	Capacitive proximity sensor with LED indicator. Power supply: 12~24Vdc. 20mA. Temperature: -20~70°C.	
CPL-X10P	Range: 30 mm. Dimension: 85 x Ø18mm. Output: NPN 100mA.	\$90.00



Counters / Timers

CT1-6D2 Timer/counter

**Programmable digital counter/timer.**

Digits: 6 digit LED. 2 presets.
 Power supply: 240Vac.
 Output: 2 x Relay SPDT. 3A, 250Vac.
 Sensor power: 12Vdc, 60mA.

Counter.....

Mode: Up count.
 Reset: External, Auto, Manual.
 Pre-scale: 000.000~999.999
 Input: Contact. 30 Hz max.
 Solid state. 6~30Vdc. 3k Hz max.

Timer.....

Mode: On delay.
 Reset: External, Auto, Manual.
 Input: External gate for timer hold.
 Ranges: 4 selectable ranges,
 9999H59M, 9999M59S, 99999.9S, 999.999S

MODEL	SIZE	PRICE
CT1-6D2	96 x 48	\$278.00

CT3-4D2 Timer/counter

**Programmable digital counter/timer.**

Digits: 4 digit LED. 2 presets.
 Power supply: 240Vac.
 Output: 2 x Relay SPDT. 3A, 250Vac.
 Sensor power: 12Vdc, 20mA.

Counter.....

Mode: Up count.
 Reset: External, Auto, Manual.
 Pre-scale: 000.000~999.999
 Input: Contact. 30 Hz max.
 Solid state. 6~30Vdc. 3k Hz max.

Timer.....

Mode: On delay.
 Reset: External, Auto, Manual.
 Input: External gate for timer hold.
 Ranges: 4 selectable ranges,
 99H59M, 99M59S, 999.9S, 99.99S

MODEL	SIZE	PRICE
CT3-4D2	48 x 48	\$185.00

TC-49 Timer/counter

**Programmable digital counter/timer.**

Digits: 6 digit LED.
 Power supply: 110/240Vac.
 Sensor power: 12Vdc, 50mA.

Counter.....

Mode: 7 counting versions.
 Reset: External.
 Input: Contact. 30 Hz max.
 Solid state. 3k Hz max.

Timer.....

Mode: Up
 Reset: External.
 Input: Contact.
 8 Ranges: From 99H59M59S to 999.999S

MODEL	SIZE	PRICE
TC-49	96 x 48	\$195.00

Counters / Timers

Programmable digital counter.

Digits: 6 digit LED. 1 preset.
 Power supply: 110/220Vac.
 Mode: Up/down/reversible.
 Reset: Panel/remote, Auto/man.
 Input: Contact. 30 Hz max.
 Solid state. 3k Hz max.
 Output: Relay SPDT. 3A, 250Vac.
 Sensor power: 12Vdc 50 mA.

H7N-6DM

Counter.



MODEL	SIZE	PRICE
H7N-6DM	72 x 72	\$260.00

Programmable digital counter.

Digits: 5 digit LED. 1 preset.
 Power supply: 220Vac.
 Mode: Up count.
 Reset: Panel, Auto/man.
 Input: Contact. 30 Hz max.
 Solid state. 3k Hz max.
 Output: Relay SPDT. 3A, 250Vac.
 Sensor power: 12Vdc 20 mA.

H7K-525U

Counter.



MODEL	SIZE	PRICE
H7K-525U	48 x 48	\$200.00

Analogue timer.

Power supply: 220Vac.
 Mode: 1 preset. On delay.
 Start/reset: Power on/off.
 Ranges: 4 selectable ranges, 6 sec, 60 sec, 6 min, 60 min.
 Relay rating: 3A, 250Vac.
 Price includes 8 pin base.

H2K

Timer



- H2K1** 1 timed SPDT.
- H2K2** 1 timed DPDT.
- H2K3** 1 timed SPDT. 1 instant SPDT.

MODEL	SIZE	PRICE
H2K-	48 x 48	\$36.00

Digital timer.

Digits: 5 digit LED. 1 preset.
 Power supply: 220Vac.
 Mode: On delay.
 Start/reset: Power on/off.
 Input: External gate for timer hold.
 Output: Relay SPDT. 3A, 250Vac.
 Ranges: 4 selectable ranges,
 999.99S, 999M59S,
 9H59M59S, 999H59M.

H5K-525U

Timer



MODEL	SIZE	PRICE
H5K-525U	48 x 48	\$185.00

Programmable digital timer.

Digits: 6 digit LED. 1 preset.
 Power supply: 110/220Vac.
 Timing: Up/down.
 Mode: 8 operation modes.
 Start/reset: Panel/remote, Auto/man.
 Input: External gate for timer hold.
 Output: Relay SPDT. 3A, 250Vac.
 Ranges: 8 selectable ranges, from 99H59M59S to 999.999S.

H5N-6DM

Timer



MODEL	SIZE	PRICE
H5N-6DM	72 x 72	\$230.00