

Pressure transmitters

JUMO



Midas S05

Bar
-1 / +9
-1 / 24
0.25 *
0.4 *
0.6 *
1.0
1.6
2.5
4
6
10
16
25
40
60

Bar
100
250
400
600

Midas HP

Bar
-1 / 0
-1 / 9
0.25
0.4
0.6
1
2.5
4
6
10
16
25
40
60
100
160
250
400
600
0 - 0.6 bar absolute
0 - 1 bar absolute

P30-504



P30-571

Bar
0.25
0.4
0.6
1
4
6
10
16
25



P30-613

Bar
0.4
0.6
1

Midas pressure transmitters.

www.intech.co.nz/midas

MODEL	DESCRIPTION	PRICE
Midas S05	Pressure transmitter. 2 wire, loop powered. Protection: IP65. Process connection: ¼" BSP. Wetted parts: Stainless steel. Mounting position: Unrestricted. Temperature: Medium, -30~125°C. Ambient, -20~125°C. Output: 4~20mA. 2 wire, loop powered. U _T = 10~30Vdc. Load resistance: R _L = (U _S -10V) / 0.02A. max. Range: Ranges in gauge pressure: from -1~9 bar to -1~24 bar. and from 0~1.0 bar to 0~60 bar.	\$398.00
* Midas SI	Range: from 0~0.25 bar to 0~0.6 bar. JUMO Datasheet: S05 = 40.1010 SI = 40.1006	\$398.00
Cable	Angled socket M12 2m cable	\$55.00
Midas HP	High pressure version of Midas S05 / SI - as above except: Range: from 0~100 to 0~600 bar. JUMO Datasheet: 40.1005	\$498.00

www.intech.co.nz/p30

dTRANS P30 pressure transmitter.

P30-504 P30-571 P30-613	Pressure transmitter. 2 wire, loop powered. Protection: IP65. Wetted parts: Stainless steel. Mounting position: Unrestricted. Temperature: Medium, -30~120°C. Ambient, -20~100°C. Output: 4~20mA. 2 wire, loop powered. U _T = 10~30Vdc. Load resistance: R _L = (U _S -10V) / 0.02A. max. Range: Ranges in gauge pressure: from -1~0 bar to -1~9 bar. and from 0~0.25bar to 0~600bar. Also some ranges in absolute pressure are available. Standard: Process connection: ½" BSP. Flush diaphragm: Process connection: ¾" BSP. Sanitary: Process connection: 1½" triclover. JUMO Datasheet: 40.4366	\$965.00 \$998.00 \$1055.00
Midas ¼" BSP Adaptor	Fittings: Adaptor to ¼" BSP taper c/w Teflon Crush Washer.	\$36.00
Midas ¼" NPT Adaptor	Adaptor to ¼" NPT taper c/w Teflon Crush Washer.	\$36.00
P30 ½" Adaptor	Adaptor to ½" BSP taper c/w Teflon Crush Washer.	\$55.00

EINTEK



LR-Display shown with JUMO P30-504 Pressure Transmitter.

LR-Display Plug in Display. Loop powered.

MODEL	DESCRIPTION	PRICE
LR-Display	Plug in Display. Loop powered. Input: 4~20mA, 2 wire. Display: 4-digit: 7.6mm height. Housing: Plastic. Protection: IP65.	\$290.00