

SD16A - Digital Indicator.

- ◆ Microprocessor based. 4 digit display.
- ◆ Inputs: Thermocouple, RTD, Current, Voltage.
- ◆ Display accuracy of $\pm(0.3\% \text{ FS} + 1 \text{ digit})$.
- ◆ Analogue output.

- ◆ Two alarm relay outputs SPST.
- ◆ Comms: RS232C, RS485 Modbus/Shimaden.
- ◆ IP66 front panel.
- ◆ LED display with 20mm high digits.
- ◆ Optional power supply of 24Vac/dc.

MODEL	SIZE	BASE PRICE	OPTIONS	ADD PRICE
SD16A	96 x 48	\$279.00	Alarms	\$60.00
			Retransmission (with Alarms) OR Sensor Supply 24Vdc 25mA	\$160.00
			Retransmission (without Alarms) OR Sensor Supply 24Vdc 25mA	\$100.00
			24Vac/dc power supply	\$50.00
			Comms RS232, RS485 Modbus/Shimaden	\$120.00

Notes:

Specify 4~20mA when ordering.
Can have either Retransmission
OR Sensor supply (not both).



www.intech.co.nz/sd16a

NEW SD24 - High Accuracy Digital Indicator.

- ◆ Microprocessor based. 5 digit display.
- ◆ Inputs: Thermocouple, RTD, Current, Voltage.
- ◆ High display accuracy of $\pm(0.1\% \text{ FS} + 1 \text{ digit})$.
- ◆ 3 Display modes: Peak hold, Bottom hold, Display hold.
- ◆ External control input (2 points) standard.

- ◆ 2 or 4 Relays for events.
- ◆ Comms: RS232C, RS485 Modbus/Shimaden.
- ◆ IP66 front panel.
- ◆ LED display with 14.3mm high digits.
- ◆ Optional power supply of 24Vac/dc.

MODEL	SIZE	BASE PRICE	OPTIONS	ADD PRICE
SD24	96 x 48	\$430.00	Alarms x2	\$60.00
			Alarms x4	\$90.00
			Retransmission	\$100.00
			24Vac/dc power supply	\$50.00
			Comms RS232, RS485 Modbus/Shimaden	\$120.00

Note:

Can have either Retransmission
OR Comms (not both).



www.intech.co.nz/sd24

KR16 - Selector switch.

- ◆ Six way selector.
- ◆ Two pole push button switches.
- ◆ Panel mount.
- ◆ Ideal for use with the SD16A or SD24 digital indicators.

MODEL	SIZE	PRICE
KR16	96 x 48	\$400.00



www.intech.co.nz/kr16